

TALCO

COOLANT GUN

Mfg. By



ShiftAir®
Beyond the limits...



SALIENT FEATURES

OVER ALL DIMENSIONS	: 210X110X40 MM
MATERIAL	: ZINC ALLOY & BRASS
WEIGHT	: 0.375 KG
WORKING PRESSURE	: UP TO 20 BAR
TEMPERATURE	: UPTO 80 DEG. CELCIUS
FLOW RATE	: ADJUSTABLE
POLYMER COATED ERGONOMIC HANDLE FOR EASY AND FIRM GRIP	

USAGE INSTRUCTIONS



LEVER

Spring loaded lever provided for smooth functioning of the Gun.



HANGING CLAMP

Spring Steel hanging clamp is provided for suitable mounting on machine.



JET ADJUSTING KNOB

This knob at the outlet of the gun is used to change the shape of the coolant jet. By rotating this knob, we can change the shape of the outgoing coolant jet from a concentrated thick stream to a fine spray.



FLOW ADJUSTING KNOB

This knob is used to preset the maximum flow of the coolant.



GUIDE FOR CONNECTIONS

TALCO Coolant Gun is fitted with a metallic push clamp fitting for 12 mm OD tube.(Optional) Tube mounting can be customized as per requirement.

Mfg. By :

ShiftAir India Pvt. Ltd.

An ISO 9001:2008 Certified Co

Plot No. 110 & 119, Sector-68, IMT, Faridabad - 121004 (Haryana) INDIA

M. : +91- 7669119185 | E-mail : sales@shiftair.co.in

Web : www.shiftair.in